

Milk Fat Control

Up to 60% milk fat concentration



Kemtrak NBP007

Main features:

- 0.001 - 60% milk fat measurement
- Real time, in-line measurement
- Robust hygienic TriClamp probe design
- Patented NIR Measurement technique
- Display in NTU, FTU, ppm, mg/l, g/l or %
- 4-20 mA current output
- Alarm signals for data and system failures
- Data and event log for quality control and validation

The Kemtrak NBP007 NIR backscatter photometer utilizes a revolutionary new and patented measurement technology that enables extremely high suspended solids measurement. This technology is particularly applicable to dairy applications as it can accurately measure milk fat samples up to 60% concentration.

Traditional turbidity based optical measurement instruments lack resolution and stop working at approximately 1% milk fat due to the extremely high optical density of the sample. This limitation is overcome with the NBP007 and for the first time the operator can monitor and have complete control over their dairy processes.



KEMTRAK

Interested in cost reduction & improved product quality?

- **reduce set-up times**
Our customers report massive reduction in separator start-up times
- **prevent product loss**
Avoid phase inversion by accurately monitoring changes leading up to this.
- **product differentiation**
Measure minute variations between products and grades of product.
- **product damage**
Measure minute changes resulting from pumping & other sources of shear.
- **interface detection**
product-water, product-product
- **monitor, control & optimize CIP cycles**
- **milk fat & solids measurement**
- **leak detection**
- **detect transition points**
- **reduce waste & wastewater costs**
- **increase product consistency**

A wide range of applications exist throughout the dairy process for in-line analysis, control and optimization using Kemtrak process photometers.

By knowing exactly what is happening at all times, process changes can be quickly implemented that result in substantial cost savings.

The Kemtrak NBP007 utilizes a robust hygienic TriClamp process connection that is designed to withstand the temperatures, pressures and chemicals present in CIP cycles. Fiber optics are used to pipe light to the measurement point and back and the measurement probe contains no electronics or serviceable parts. The TriClamp measurement probe is suitable for all pipe diameters from DN25 / 1" using a suitable pipe bend adapter.

All Kemtrak's products are made from the highest quality materials and are designed to the most demanding specifications to ensure long life and extremely low maintenance.



Measurement Principle

Patented NIR backscatter photometric technique

Measurement Range

LOW 0.001% (ca. 20NTU) - 10% milk fat
HIGH 1% - 60% milk fat

Measurement range is factory configured

In-line Hygienic Fiber Optic Measurement Probe

Process connection: Tri-Clamp® (ISO 2852 & DIN 32676)

Line size: DN25 (1") and above

Material: Stainless steel EN 1.4435 (316L)

Surface Finish: Ra < 0.4 µm

Temperature: 140°C (284°F) (process & ambient)

Process Pressure: 10 mbar to 10 bar

Cable length: 5m standard
other lengths available on request

Light Source

High performance near infra-red (NIR) light emitting diode
Typical NIR lamp lifetime: >100 000 hrs

Control Unit Housing

Glass-fibre reinforced polyester & polyester front panel
Captive lid screws & wall mounting brackets stainless steel
220 x 120 x 90 mm (8.66 x 4.72 x 3.54 inch) L x W x D
IP 65 / EN 60529

Display

16 x 2 alphanumeric dot matrix LCD display
LED background illuminated
Display update: 0.5 seconds
Display units: NTU, FTU, ppm, mg/l, g/l, EBC or %.
User configurable
LED 1 (green): power on
LED 2 (red): alarm
LED 3 (red): clean

Operation

4 push buttons

Software Features:

- Auto gain: Gain switching is fully software controlled
- Calibration: Concentration & mA output
- Damping: from 0 to 9999s with noise (air bubble / particle) filter
- Memory: Non volatile - configuration and data retained upon power failure
- Security: Alphanumeric password protection
- Clean: Automatic cleaning control
- PID: Input PID controller - Pulse width modulated relay output or 0/4-20mA output

Data Logger

- 6 900 data points (timestamp, average, max. & min.), ring buffer
- Configurable log time interval 1s to 24hr

Event Logger

- 10 000 events
- Alarms, zeroing, cleaning, calibration & system events (power, system failures, high/low system temperature)

Remote Input

- 1 x Digital input (potential free contact) for:
- Auto clean
 - Hold output

mA Output

1 x 0/4 - 20 mA galvanically isolated
Accuracy: <0.2%
Resolution: < 0.05%
Load: 0 - 400 Ohm

Relay Outputs

2 x 0.5A 240VAC User configurable (alarm, PID, system fault)
1 x 0.5A 240VAC Automatic cleaning control
PTC resistor fuses in series with the relays
LED status indicators flash when relays are active

Fail-Safe:

Relay output & 0/4-20mA value

PC Communications

USB (mini-USB connector)

Power Supply

115/230V AC selectable, 50-60Hz, 1A

Power Consumption

25 VA (max.)

Control Unit Operating Conditions

Ambient temperature: -10°C to +50°C (14°F to 122°F)
Transport: -20°C to +70°C (-4°F to 158°F)

Certificates

CE, ISO 9001:2000.



Kemtrak AB • Box 2940 • SE-187 29 Stockholm • Sweden
Info@kemtrak.com • www.kemtrak.com

Distributor

Techmation b v.

P.O. box 195
NL - 4250 DD Werkendam

Phone +31.183.500.331 www.techmation.nl
Fax +31.183.500.342 sales@techmation.nl

Kemtrak is a leading manufacturer of fiber optic measuring and automation products for the process engineering industry. The Company provides tailor made solutions to meet the needs of a wide range of industries including pulp and paper, food & beverages, chemical, petrochemical, pharmaceutical and water & environment. With its headquarters in Stockholm, Sweden, Kemtrak has distributors in 20 countries around the world. The main manufacturing facility in Gothenburg, Sweden is certified according to ISO 9001:2000.

We reserve the right to make changes without previous notice. Kemtrak is a registered trademark of Kemtrak AB.